

Océ TDS320

System data



Océ TDS320

Effortless workflow, true reliability

Océ TDS320 Printer technology

<i>Technology</i>	Electrophotography (LED) with Organic Photoconductor drum
<i>Resolution</i>	600 dpi
<i>Printer optimisation</i>	User specified print optimisation modes: Lines&text for excellent line accuracy; Standard for excellent lines plus smooth grays; Poster for excellent grays and smooth solid fills.
<i>Fusing technology</i>	Océ Radiant Fusing, instant heating
<i>Toner system</i>	Clean closed toner system, refill while printing

Throughput

<i>Speed</i>	Constant 3 linear metres p/min or a 1.8 Ao p/min in all print modes
<i>Warm-up time</i>	None, instant behaviour
<i>Paper path</i>	Optimised, continuous printing speed when printing jobs from different rolls

Document delivery



- Standard: integrated tray, no extra footprint, delivery at the front.
- Optional with 2 rolls version: integrated Compact Output Stacker for up to 100 prints neatly stacked with no extra footprint, delivery at the front.



Océ TDS320 System data

Media

<i>Media sources</i>	Choice of 1 or 2 rolls version plus manual feed
<i>Media capacity</i>	Up to 175 meters per roll (75 gr/m ² paper) with automatic switching when roll is empty
<i>Media types</i>	Plain, transparent, recycled, fluorescent and coloured paper, films and vellums. Up to 110 gr/m ²
<i>Media trimming</i>	Closed system protects cutting device
<i>Output sizes</i>	From A3 to A0 and 36", up to 15 metres long

Environment

<i>Dimensions</i>	1352 mm(W)× 899 mm(D) × 1251 mm(H)
<i>Weight</i>	175 kg (1 roll version), 185 kg (2 roll version)
<i>Main supply</i>	100/120/230 V, 50/60 Hz
<i>Power consumption</i>	EPA Energy Star® compliant, Operating 1340 W, Standby 28 W, and Sleep mode 6 W
<i>Sound pressure</i>	Sleep mode 0 dB (A), Standby 24 dB (A) Operating 54 dB (A) according to EN7779 operator position
<i>Safety approvals</i>	TüV GS, CETECOM, CE, (c)UL, FCC

Océ Power Logic® Controller

<i>Platform</i>	Océ Controller with Windows®XP embedded
<i>Memory</i>	512 Mb, expandable to 1024 Mb
<i>Graphic user interface</i>	Optional Monitor (17" CRT and 17" flat panel)
<i>Interfaces</i>	Standard: Ethernet 100/10 Mb/s with RJ45
<i>Network protocols</i>	TCP/IP, NetBEUI (smb), Novell (IPX/SPX), FTP, LPD. Other protocols supported through an external print server
<i>Power consumption</i>	< 62.5 W controller
<i>Main supply</i>	120/230 V, 50/60 Hz
<i>File formats</i>	HPGL, HPGL2, Calcomp 906/907/951 HPRTL, TIFF 6.0, CALS1, NIRS, C4, ASCII, optional Adobe® PostScript® 3™/PDF
<i>Functionality</i>	■ File spooling on the controller ■ Concurrent receiving / processing / printing ■ Océ Settings editor application: edit and save customised system settings ■ Special modes: Standard, lines & text and Poster

- Multiple prints: up to 999
- Automatic language sensing
- Automatic roll selection and switching
- Plot manipulation: rotation, autoscaling and positioning
- Pen management

Océ Remote Logic® application

Local and remote user communication system with:

<i>Settings Editor</i>	Edit and save customised system settings application:
<i>Supported operating systems</i>	Windows 95, 98, Me, 2000, NT4.0 SP3 and XP. On any other platform and operating system supporting Java 1.1.8 or higher

Océ TDS320 Scanner

<i>Technology</i>	CCD, Océ Image Logic® real time image processing hardware
<i>Speed</i>	3 metres p/min
<i>Original feed</i>	Face down, right aligned. Automatic feed on/off. Rewind original to front on/off
<i>Originals</i>	Image width: 210 - 914 mm Original width: 210 - 1020 mm Original length: 210 mm - 15 m
<i>Maximum thickness</i>	1,5 mm
<i>Exposure control</i>	Automatic background compensation (on/off) manual fine adjustment
<i>Special modes</i>	Line & Text, Photo and Blueprint
<i>Reproduction scale</i>	25% to 400%, adjustable in 1% and programmable fixed steps
<i>Scan-to-file zoom</i>	50% to 200%
<i>Other operating functions</i>	■ Concurrent copying and printing ■ Multicopy mode: 1-99 copies (scan once print many) ■ Programmable default settings ■ Standard cut or synchro cut modes ■ Leading- and trailing-edge adjustment (add or remove up to 400 mm) ■ Image mirroring
<i>Power consumption</i>	EPA Energy Star® compliant, Operating 140 W, Standby 27 W
<i>Main supply</i>	100/120/230 V, 50/60 Hz
<i>Dimensions</i>	1240 mm (W) × 615 mm (D) × 1105 mm (H)
<i>Weight</i>	65 kg



Océ TDS320 System data

Océ Scan Logic®


Océ Scan Logic is an optional scan-to-file software application for the Océ TDS320 multifunctional system.

<i>Applications</i>	Océ Scan Manager, integrated scanning solution and Océ View Station LT for viewing
<i>Scan destinations</i>	6 programmable destinations Scan to Web using FTP Scan to network directory Scan to controller
<i>Resolutions</i>	200, 300, 400 dpi
<i>Data formats</i>	Tiff (G3, G4, uncompressed) CALS Type 1 PDF
<i>Scan modes</i>	Single scan, stream feed productive batch scanning with or without check plot
<i>File naming</i>	Automatically generate unique file names for each scan, change file names at point of scanning
<i>Viewing</i>	View scans at point of scanning
<i>Océ Image Logic</i>	Optimum scan quality with special original modes
<i>Optimisation</i>	Scan quality or file size
<i>Ease of use</i>	Scan to file from scanner panel, scan directly to destination
<i>Options</i>	■ Océ View Station for editing and enhancement of scanned documents ■ Océ Batch Processor for automated editing
<i>Minimum requirements</i>	Graphical user interface on Océ Power Logic Controller



Drivers and job-submission software

<i>Océ HDI driver</i>	For AutoCAD (LT) 2000, 2000i, 2002, 2004, 2005 and 2006
<i>Océ WPD</i>	Windows 2000, XP, Windows Server 2003, Windows Terminal Server, Citrix Metaframe
<i>Océ Adobe PostScript®3 drivers</i>	Windows 95, 98, ME, NT4.0, 2000, XP and Mac OS 9, X
<i>OcéPrintExec®LT (optional)</i>	Individual Windows-based productive job creation and submission application with direct device feedback for Windows 2000, XP, and Windows Server 2003



For information and services, visit us at www.oce.com



Printing for Professionals

© 2005 Océ. Illustrations and specifications do not necessarily apply to products and services offered in each local market.

Technical specifications are subject to change without prior notice. Océ, Océ Power Logic, Océ Remote Logic, Océ Image Logic, Océ Scan Logic and Océ Print Exec Workgroup, are registered trademarks of Océ-Technologies B.V. All other trademarks are the property of their respective owners.